## Grande Prairie Scissor Lift License

Grande Prairie Scissor Lift License - The is an inherent chance in operating a scissor lift, since with all types and kinds of powered work tools will require proper handling to be able to prevent accidents which may result in injuries or damage. Businesses have to make sure that workers operating this equipment have the necessary experience.

Businesses should not permit scissor lifts to be used by unqualified people. The scissor lift is designed to raise people to high levels. Failure to understand and completely abide by safety standard could cause damage to the lift or injuries for users.

For those who use scissor lifts, there is no legislation governing the utilization of fall protection. Nonetheless, manufacturers can recommend the utilization of fall protection and in several situations tying off in scissor lifts might be required by employer guidelines, local rules or job-specific risk assessment.

To be able to make certain that the scissor lift is in good working condition prior to utilizing the machinery, the operator has to perform a thorough check. This is the operator's task, even if the unit has already been in service that same day. The machine's operator's manual contains a checklist for pre-operation.

Examples of what to look for when doing a pre-operation inspection consist of checking tire-inflation pressure, and checking ground controls and controls in the platform to ensure they are working. When retracting or extending the boom, watch for delayed movement on the fly section which can indicate cables are loose. When operating the controls, make sure that the emergency stop switches work. Operate functions against the equipment's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters must automatically stop the unit before it moves into an unstable position, if they are working correctly. If they aren't, shut down the lift and ensure that it is fixed before utilizing it again.

Safe and proper operating measures should be followed at all times. Levers must be operated with controlled, even pressure. A control lever should never be pushed from one position to the opposite position. The lever must be shifted to neutral, prior to stopping, and then proceeding in the desired direction. When released, levers and control switches should return to the neutral position automatically. Depress the foot switch before operating platform controls.